CSI WATER TREATMENT SYSTEMS

# Whole House Filter

| General Specifications | WF10-S3 | WF15-S3 | WF20-S3 | WF25-S3 | WF30-S3 |
|---|---|---|---|---|---|
| Filter Media Type | Less Filter Media | | | | |
| Filter Media Capacity (cu ft) | 1.0 | 1.5 | 2.0 | 2.5 | 3.0 |
| Mineral Tank Size | 9 x 48 | 10 x 54 | 12 x 52 | 13 x 54 | 13 x 65 |
| Service Flow Rate - Continuous (gpm) | 4 | 5 | 6 | 8 | 9 |
| Service Flow Rate - Intermittent (gpm) | 6 | 7 | 8 | 10 | 11 |
| Backwash Flow Rate (gpm) | 5.0 | 5.0 | 6.0 | 7.0 | 7.0 |
| Gallons Used / Backwash | 100 | 100 | 120 | 140 | 140 |
| Space Required (D x W x H) | 9 x 9 x 56 | 10 x 10 x 62 | 12 x 12 x 60 | 13 x 13 x 62 | 14 x 14 x 74 |
| Approximate Shipping Weight (lbs) | 27 | 32 | 35 | 40 | 49 |

## System Features

- Signature 3 Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Includes meter to provide water usage history
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- Vortech™ distributor plate
- Adjustable Cycle Times
- High Backwash flow capability
- Proprietary two valve bypass with 1” MNPT Connections
- Weather / Insect Resistant One-Piece Slide Cover
- Optional dome fill hole and closure
- Optional "natural" color
- No chemical regenerants required

* - Use of a Flow Control in the service line is highly recommended.
** - Caution should always be used in sizing filters. Always choose a unit by first satisfying the backwash and flow requirement. Consult the factory or your field sales person with questions.